

GT1080HDR

Exceptional short throw, 120Hz, huge-screen gaming









- Incredible 3,800 lumens and 50,000:1 contrast ratio
- Short throw 0.5:1 projection lens
- 4K UHD and 1080p HDR (HDMI 2.0) input compatible
- Enhanced Gaming Mode delivers up to 8.4ms response time at 1080p, 120Hz



Elevate your gaming experience with the short throw, 1080p, 3,800 lumens Optoma GT1080HDR. Enhanced Gaming Mode combined with a 120Hz refresh rate enable blur-free visuals with lightning-fast, 8.4ms response time for a competitive gaming advantage.

Specifications

Display/image
Display technology

□ DLP™

Resolution 1080p Full HD (1920x1080)

 Brightness
 3,800 lumens

 Contrast ratio
 50,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3,16:9

 Keystone correction - vertical
 +/-40°

 Horizontal scan rate
 15.38 ~ 91.15Khz

 Horizontal scan rate
 15.38 ~ 91.15Khz

 Vertical scan rate
 50 ~ 85(120 for 3D)Hz

Uniformity 70%

Screen size 36.2" ~ 307.8" diagonal

Lamp info
Light source type
Lamp watts
Lamp

Lamp life hours (up to) 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

 Optical

 Throw ratio
 0.49:1

 Projection distance
 15.75" - 133.86"

 Focal length (mm)
 7.42mm/0.292"

 Native offset
 116%

Connectivity

Connections Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL, 1 x

VGA (YPbPr/RGB), 1 x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

 General
 Noise level (typical)
 26dB

 Noise level (max)
 28dB

PC compatibility UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA,

VGA, Mac

2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D

3D Full 3D

 Security
 Security bar, Kensington Lock, Password protected interface

 OSD / display languages
 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Data remote with laser and mouse function

 Speaker count
 1

 Watts per speaker
 10W

 In the box
 AC power cord

Remote control

2x AAA batteries

Basic user manual

100 ~ 240V, 50 ~ 60Hz

Optional wireless models WHD200

Power
Power supply
Power consumption (standby)

 Power consumption (standby)
 0.5W

 Power consumption (min)
 200W

 Power consumption (max)
 285W

Weight and dimensions

Dimensions (W x D x H) 12.44" x 9.61" x 4.25"

 Gross weight
 8.6 lbs

 Net weight
 6.61 lbs





